

25D

系列  
SERIES

PU on Plastic Core (Black)



Wheel Features

Tread Material:	PU	Core Material:	High Strength PP
Bearing:	Ball Bearing	Tread Hardness:	95A±3
Temperature:	-20°C~50°C	Running Speed:	4km/h

Note: Use beyond temperature range or beyond the recommended speed may shorten product life or even damage the product.



- ✔ 2 precision ball bearings,flexible rotation
- ✔ Injection polyurethane,glue-free self lock structureoil resistance,wear resistance
- ✔ Environmental protection,quiet,effectively protect the floor
- ✔ With plastic covers,thread-proof design
- ⚠ High temperature and humidity may shortened service life






Rolling resistance	■ ■ ■ ■ □	Very good
Wear resistance	■ ■ ■ ■ ■	Excellent
Operating noise	■ ■ ■ ■ □	Very good
Floor surface preservation	■ ■ ■ ■ □	Very good


Bracket Features

- ✔ Stable braking effect
- ✔ Spindle equipped with precision bearing,quiet and flexible
- ✔ Bracket made of pressed steel plate,firm and strong
- ✔ No-swing design:caster stops swing immediately after being held horizontally
- ✔ Powder spray treatment,superior anti-rust and anti-corrosion performance,salt spray test over 72 hours
- ⚠ Wheel brake only,without direction lock function

Parameter (mm)							
Wheel Size	Capacity	Wheel Dia.	Wheel Width	Total Height	Offset	Swivel Radius	Swivel Radius
5"	130 kg	125	38	168	35	97.5	126
6"	150 kg	150	38	195	35	110	126



Mounting Drawing




Product ID			
Product Images			
Wheel Size	Plate swivel	Plate fixed	Plate swivel brake
5"	25D03-1373	25D01-1373	25D02-1373
6"	25D06-1374	25D04-1374	25D05-1374

Product Details



Double bearing steering structure is quiet and flexible.

The structure of the steering stop can immediately stop the shaking in the suspended or horizontal state and ensure smooth rotation in the vertical state.



Electrophoretic scaffolds have better anticorrosion performance.



Dust cover can effectively protect the bearing and prevent winding.

