

35D 系列 PU on Plastic Core (Blue)



Wheel Features

Tread Material:	Supper PU	Core Material:	High Strength PP
Bearing:	Delrin	Tread Hardness:	95A±3
Temperature:	-20°C~50°C	Running Speed:	4km/h



Note: Use beyond temperature range or beyond the recommended speed may shorten product life or even damage the product.

- ✔ Delrin bearing, waterproof, rust-proof
- ✔ Advanced injection polyurethane, glue-free self lock structure oil resistance, wear resistance
- ✔ Environmental protection, quiet, effectively protect the floor
- ⚠ High temperature and humidity may shortened service life





Rolling resistance	■ ■ ■ ■ □	Very good
Wear resistance	■ ■ ■ ■ ■	Excellent
Operating noise	■ ■ ■ ■ □	Very good
Floor surface preservation	■ ■ ■ ■ □	Very good


Bracket Features

- ✔ ON/OFF pedals, stable braking effect, easy to operate
- ✔ 304 Stainless Steel material pressed and welded, anti-rust and anti-corrosion
- ✔ Dustproof ring effectively protects grease for long sevice life
- ✔ Polishing treatment, exellent appearance

Parameter (mm)	Capacity (KG)	Wheel Dia.	Wheel Width	Total Height	Offset	Swivel Radius	Swivel Radius
4"	180 kg	100	45	145	34	84	141
5"	210 kg	125	48	165	38	100.5	141
6"	260 kg	150	50	190	44	119	141
8"	280 kg	200	50	240	54	154	154



Mounting Drawing



Product ID

Product Images



Wheel Size

Plate swivel

Plate fixed

Plate swivel
brake

4"

35D01-1411

35D03-1411

35D02-1411

5"

35D04-1412

35D06-1412

35D05-1412

6"

35D07-1413

35D09-1413

35D08-1413

8"

35D10-1414

35D12-1414

35D11-1414

Product Details

ON/OFF brake is easy to operate. Brake components can be replaced with screw connecting.



Grease nipple is convenient for maintenance. Dust ring protection can effectively dust and protect grease embellish.



According to the using environment, can match terling, stainless iron or stainless steel bearings.

