

Wheel Features

Tread Material:	Rubber	Core Material:	Cast Iron
Bearing:	Ball Bearing	Tread Hardness:	85A±3
Temperature:	-20°C~50°C	Running Speed:	4km/h

Note: Use beyond temperature range or beyond the recommended speed may shorten product life or even damage the product.



- ✔ 2 precision ball bearings,flexible rotation
- ✔ Natural rubber material,vulcanized,high rebound
- ✔ Environmental protection,quiet,effectively protect the floor
- ✔ Painted,anti-rust and anti-corrosion
- ⚠ Biodegradable rubber material,recommended to use within 3 year of production for best performance






Rolling resistance	■ ■ ■ □ □	Good
Wear resistance	■ ■ ■ ■ □	Very good
Operating noise	■ ■ ■ ■ ■	Excellent
Floor surface preservation	■ ■ ■ ■ ■	Excellent

Bracket Features


- ✔ Steel plate pressed and fully welded,firm and strong
- ✔ Thickened top plate,resistant to compress which is hard to deform
- ✔ Plane bearing,high load capacity,impact resistance and flexible steering
- ✔ Blue galvanized,ROHS/REACH passed,salt spray test over 72 hours
- ✔ ON/OFF pedals,stable braking effect,easy to operate
- ✔ Brake part is replaceable,convenient to maintain

Parameter (mm)	Capacity (KG)	Wheel Dia.	Wheel Width	Total Height	Offset	Swivel Radius	Swivel Radius
5"	300 kg	125	48	176	38	101	151
6"	350 kg	150	48	201	44	119	154
8"	400 kg	200	48	252	54	154	173



[English]

Mounting Drawing



Product ID			
Product Images			
Wheel Size	Plate swivel	Plate fixed	Plate swivel brake
5"	36A04-1146	36A06-1146	36A05-1146
6"	36A07-1147	36A09-1147	36A08-1147
8"	36A10-1148	36A12-1148	36A11-1148

Product Details



ON/OFF brake is easy to operate. Brake components can be replaced with screw connecting.



Planar bearings can match high loading capacity, impact resistance and flexible in rotation.

Double-sides welding, firm and strong. The top plate is thickened by 7.5mm.



The natural rubber wheel has high rebound properties to protect the floor. Iron cover looks nice and anti-winding.

