

Wheel Features

Tread Material:	Rubber	Core Material:	Cast Iron
Bearing:	Ball Bearing	Tread Hardness:	85A±3
Temperature:	-20°C~50°C	Running Speed:	4km/h

Note: Use beyond temperature range or beyond the recommended speed may shorten product life or even damage the product.



- ✔ 2 precision ball bearings,flexible rotation
- ✔ Natural rubber material,vulcanized,high rebound
- ✔ Environmental protection,quiet,effectively protect the floor
- ✔ With iron covers,thread-proof design
- ✔ Painted,anti-rust and anti-corrosion
- ⚠ Biodegradable rubber material,recommended to use within 3 year of production for best performance





Rolling resistance	■ ■ ■ □ □	Good
Wear resistance	■ ■ ■ ■ □	Very good
Operating noise	■ ■ ■ ■ ■	Excellent
Floor surface preservation	■ ■ ■ ■ ■	Excellent


Bracket Features

- ✔ ON/OFF pedals,stable braking effect,easy to operate
- ✔ Steel plate pressed and fully welded,firm and strong
- ✔ Dustproof ring effectively protects grease for long sevice life
- ✔ Good damping performance,effective buffer,ensure balance and stability
- ✔ Galvanized,salt spray test over 72 hours
- ⚠ Wheel brake only,without direction lock function

Parameter (mm)							
Wheel Size	Capacity	Wheel Dia.	Wheel Width	Total Height	Offset	Swivel Radius	Swivel Radius
5"	270 kg	125	48	185	50	112.5	175
6"	320 kg	150	48	197	50	125	183
8"	360 kg	200	48	247	63	163	190



Mounting Drawing



Product ID			
Product Images			
Wheel Size	Plate swivel	Plate fixed	Plate swivel brake
5"	45C31-1146	45C32-1146	45C33-1146
6"	45C341147	45C35-1147	45C36-1147
8"	45C371148	45C38-1148	45C39-1148

Product Details



ON/OFF brake is easy to operate.



Single spring shock absorption can effectively buffer, ensure balance and stability.

Double-welded, strong and robust. Dust ring can effectively protect the dust and grease lubrication.



The soft natural rubber wheel has high rebound properties to protect the floor. Iron cover is nice appearance and anti-winding.

